

222 Cavalcade Street, 77009-3213  
P.O. Box 8768, Houston, Texas 77249-8768  
Tel: (713) 692-9151 Fax: (713) 696-6205

*Attention: Jim Ahlander*

**FasTower**  
861 So. Center Street  
MESA, AZ 85210  
P: 602 327 1595 / F: 480/898-1444

W/O. No.: FAS002-02-10-77508-4  
P.O. No.:  
Report Date: 2/23/2011

**BREAKING STRENGTH OF WIRE ROPE FROM RETRACTABLE TOWER UNIT**


Cable Diameter (in)	Ultimate Load (lbs)	Test Notes
0.190	3,400	Sample broke in grips, meaning ultimate strength of the wire rope has not been reached
0.253	5,700	Sample broke in grips, meaning ultimate strength of the wire rope has not been reached

This document contains technical data whose export and re-export/re-transfer is subject to control by the U.S. Department of Commerce under the Export Administration Act and the Export Administration Regulations. The Department of Commerce's prior written approval is required for the export or re-export/re-transfer of such technical information to any foreign person, foreign entity or foreign organization whether in the United States or abroad.

Our letters and reports are for the exclusive use of the client to whom they are addressed and shall not be reproduced except in full without the approval of the testing laboratory. The use of our name must receive our written approval. Our letters and reports apply only to the sample tested and/or inspected, and are not indicative of the quantities of apparently identical or similar products. Unless otherwise noted all test methods and specifications are to the most current revision. Material submitted to our metals department will be discarded after a period of 30 days unless otherwise directed.

Stork SWL, is an operating unit of Stork Materials Technology B.V., Amsterdam, The Netherlands, which is a member of the Stork group

**Respectfully Submitted**

  
Terry Wilt  
Manager, Product Evaluation